

DB625 High Voltage Megohmmeter

Versatile and accurate measurements up to 1.000.000 GΩ
with tests from 50V to 5kV DC



- Available in 2 versions: 2 kV or 5 kV
- High speed testing 45 ms
- High accuracy $\pm 2\%$ to 1 TΩ
- Measurement Range from 10 kΩ up to 1 PΩ (Peta = 1.000.000 Giga Ω)
- Leakage current down to 1 pA
- Accuracy $\pm 2\%$, ± 1 pA
- Test Voltages: 50 V to 2 kV or 50 V to 5 kV in 1 V steps
- Contact Check Function
- Powerful charge capability
- Charge current: 2 kV: 2/ 12/ 50 mA
5 kV: 2/ 5/ 20 mA
- 4 ranges and/or auto range
- 5 Programmable Limits
- Designed to be used with 40 channel IR Scanner type DB640

* GENERAL:

The DB625 Megohmmeter is designed for use in various applications such as testing insulation resistance of cables and testing leakage current in capacitors.

The instrument is microprocessor controlled. The menu driven bright back-lit LCD display enables quick, logical and easy-to-use operation.

The DB625 has test voltages up to 2 kV 50 mA or 5 kV 20 mA. Suitable for HV applications such as capacitors, ariels, relays, motors etc.

The instrument can be programmed to automatically perform timed testing, consisting of up to 20 test steps, either high current charging, normal charging, or a measurement sequence. Each sequence may last up to 60 min.

The DB625 Megohmmeter also features pre-programmed sequences, for example a sequence for Quality Control, that charges until a minimum insulation resistance is reached. Then it discharges automatically.

Programmable delay of measurement: Up to 10 s in steps of 1 ms after external triggering.

The measurement results may be used for BIN sorting with one out of five limit sets.

DB625 is fitted with both standards IEEE (GPIB) and RS232 Interfaces. Also an optically insulated Handler/Limits Interface is included.

The high speed of DB625 with only 45 ms between measurements gives the possibility of implementing prediction intelligence in an external PC for very high-speed production test of capacitors.

The low input impedance of 10 kΩ for test current above 10 nA, and 1 MΩ for test current below 10 nA is also a contributory factor in reaching the high speed testing.

Automatic check of contact failure for capacitors and capacitive elements like cables is a feature implemented for high volume production. The contact check does not increase the test time.

DB625 High Voltage Megohmmeter

Specifikations



DC CURRENT MEASUREMENTS:	
Ranges:	Range 1: 1 pA to 10 nA; Zi = 1 MΩ or 10 kΩ (selectable)
	Range 2: 2 nA to 100nA; Zi = 10 kΩ
	Range 3: 20 nA to 10 uA; Zi = 10 kΩ
	Range 4: 2 uA to 1 mA; Zi = 10 kΩ
Accuracy:	±2 % of value ±1 pA
TEST VOLTAGE:	
Range:	2kV version: 50 V to 2000 V, 5kV version: 50 V to 5000 V, all in 1 V steps
Accuracy:	±2 % of value or ±1 V
Stability:	±10 ppm @ 10 % change in line voltage, ±20 ppm/degree C
Source Resistance:	2kV version: 420 Ω, 5kV version: 1200 Ω
Current Limits:	2kV: 2, 12 or 45 mA (50 mA short circuit), 5kV: 2, 5 or 18 mA (20 mA short circuit)
Switching:	Manually ON/OFF from front panel or controlled by a built-in timer, or by remote
Timing:	Programmable Fast Charging: 0 to 9999 ms (charge resistance 1200 Ω)
Programmable Measurement delay:	0 to 9999 ms
Discharge Resistance:	100 kΩ / 35 W, Max. dischargable energy for voltage > 1500V: 1500 Joule
Discharge Time:	t = 1 x Cx (in μF) with V test decreasing to 1 % of test level
RESISTANCE MEASUREMENTS:	
Range:	10 kΩ to 1 PΩ (dependent on test Voltage) (Peta = 1.000.000 Giga)
Accuracy:	For I > 100 pA: 2%
	For I ≤ 100 pA: Acc. equals the acc. of current measurement.
MEASURING SPEED:	
Trig Mode:	One Measurement: <48 ms (excl. charging)
	Average up to n = 100 measurements: <48 + (N-1) x 40 ms (excl. charging)
Continuous Mode:	Direct Reading: 90 to 4000 ms depending on average
	Bar Graph: Display update every 40 ms
DISPLAY READING:	
Direct reading:	Current or Resistance, 3,5 digits
Bar Graph:	8 ranges with 2 decades per graph with fixed- or auto scaling
x – y Graph:	Current or resistance scale vs. time scale
STANDARD FITTED INTERFACES:	
LIMITS:	5 built-in programmable limits on resistance or current
IEEE 488: (IEEE 488-1 and 2)	“Talker Only” and Talker/Listener” Modes. True sub-set of Standard protocol
RS232C:	Baud rate up to 19.200 Baud. Full two-way control/output
Control I/O:	Opt coupler input / output 25 V/10 mA. Trig, Measure END Signal, Trig Ready Signal, Data Ready Signal, Fault Signal, Limit Outputs
Ambient Temperature:	10 – 40 degrees Celsius
Power:	90 – 130 and 200 – 260 V AC 50 – 60 Hz
DIMENSIONS:	
Height:	140 mm/ 5.5 inch
Width:	438 mm/ 17.2 inch
Depth:	360 mm/ 14.2 inch
Weight:	12.5 kg/ 27.5 lbs.
ACCESSORIES SUPPLIED:	Line power connector, Two 1.5 m coax cables with H.T. BNC connectors
	Brackets for 19” rack-mounting, Manual in English
OPTIONS:	
Available in Scanner versions:	5 channels/40 Channels
Fixture for axial and radial components:	Yes
Test probe with trig contact:	Yes
© September 2008, Danbridge A/S ALL SPECIFICATIONS SUBJECT TO CHANGES WITHOUT PRIOR NOTICE	